

Klapy oddymiające KDH dwuskrzydłowe z owiewkami

L.p.	wymiary nominalne otworu [cm]		powierzchnia geometryczna [m ²]	powierzchnia czynna klapy z owiewkami [m ²]	Waga klapy [kg]	Typ napędu, pobór prądu	
	dlugość A	szerokość B					
1	150	150	2,25	1,31	56	ZA 155/800-HS; 5 A	
2	150	160	2,40	1,42	57		
3	150	170	2,55	1,50	59		
4	150	180	2,70	1,59	60		
5	150	190	2,85	1,71	62		
6	150	200	3,00	1,80	63		
7	150	210	3,15	1,89	65		
8	150	220	3,30	1,98	66		
9	150	230	3,45	2,10	68		
10	150	240	3,60	2,20	69		
11	150	250	3,75	2,29	71		
12	150	260	3,90	2,38	72		
13	150	270	4,05	2,47	79		
14	150	280	4,20	2,60	81		
15	150	290	4,35	2,70	82		
16	150	300	4,50	2,79	84		
17	160	160	2,56	1,51	59	ZA 155/800-BSY+HS Set; 10 A	
18	160	170	2,72	1,60	60		
19	160	180	2,88	1,73	62		
20	160	190	3,04	1,82	63		
21	160	200	3,20	1,92	65		
22	160	210	3,36	2,05	66		
23	160	220	3,52	2,15	68		
24	160	230	3,68	2,24	71		
25	160	240	3,84	2,34	74		
26	160	250	4,00	2,48	78		
27	160	260	4,16	2,58	79		
28	160	270	4,32	2,68	81		
29	160	280	4,48	2,78	82		
30	160	290	4,64	2,88	84		
31	160	300	4,80	2,98	85		
32	170	170	2,89	1,73	62	ZA 155/800-BSY+HS Set; 5 A	
33	170	180	3,06	1,84	63		
34	170	190	3,23	1,97	65		
35	170	200	3,40	2,07	66		
36	170	210	3,57	2,18	68		
37	170	220	3,74	2,28	69		
38	170	230	3,91	2,42	71		
39	170	240	4,08	2,53	78		
40	170	250	4,25	2,64	79		
41	170	260	4,42	2,74	81		
42	170	270	4,59	2,85	82		
43	170	280	4,79	2,95	84		
44	170	290	4,93	3,11	85		
45	170	300	5,10	3,21	87		
46	180	180	3,24	1,98	65	ZA 155/800-BSY+HS Set; 10 A	
47	180	190	3,42	2,09	66		
48	180	200	3,60	2,20	68		
49	180	210	3,78	2,31	69		
50	180	220	3,96	2,46	71		
51	180	230	4,14	2,57	78		
52	180	240	4,32	2,68	79		
53	180	250	4,50	2,79	81		
54	180	260	4,68	2,90	82		
55	180	270	4,86	3,06	84		
56	180	280	5,04	3,18	85		
57	180	290	5,22	3,29	87		
58	180	300	5,40	3,40	88		
59	190	190	3,61	2,20	68		ZA 155/800-HS; 5 A
60	190	200	3,80	2,36	69		
61	190	210	3,99	2,47	71		
62	190	220	4,18	2,59	77		
63	190	230	4,37	2,71	79		
64	190	240	4,56	2,83	81		
65	190	250	4,75	2,99	82		
66	190	260	4,94	3,11	84		
67	190	270	5,13	3,23	85		
68	190	280	5,32	3,35	87		
69	190	290	5,51	3,47	88		
70	190	300	5,70	3,59	90		
71	200	200	4,00	2,48	76	ZA 155/800-BSY+HS Set; 10 A	
72	200	210	4,20	2,60	78		
73	200	220	4,40	2,73	79		
74	200	230	4,60	2,90	81		
75	200	240	4,80	3,02	82		
76	200	250	5,00	3,15	84		
77	200	260	5,20	3,28	85		
78	200	270	5,40	3,40	87		
79	200	280	5,60	3,53	88		
80	200	290	5,80	3,71	90		
81	200	300	6,00	3,84	91		
82	220	220	4,84	3,05	82		ZA 155/800-BSY+HS Set; 10 A
83	220	240	5,28	3,33	85		
84	220	260	5,72	3,66	88		
85	220	280	6,16	3,94	91		
86	220	300	6,60	4,22	94		
87	240	240	5,76	3,69	88	ZA 155/1000-BSY+HS Set; 10 A	
88	240	260	6,24	3,99	91		
89	240	280	6,72	4,30	94		
90	240	300	7,20	4,68	97		
91	250	250	6,25	4,00	91		ZA 155/1000-BSY+HS Set; 10 A
92	250	300	7,50	4,88	98		
93	260	260	6,76	4,33	94		
94	260	280	7,28	4,73	97		
95	260	300	7,80	5,07	100		
96	280	280	7,84	5,10	100		
97	280	300	8,40	5,46	103		
98	300	300	9,00	5,94	106		