

Parametry klap jednoskrzydłowych FIRE

Lp.	Wymiary nominalne otworu [cm]			Powierzchnia geometryczna [m²]	Powierzchnia czynna [m²]			Waga klapy [kg] *	Typ napędu, pobór prądu
	Szerokość B	Długość A	Wysokość H		Klapy	Klapy z owiewkami	Klapy z owiewkami i dyszą		
1	100	100	50	1,00	0,47	0,77	0,82	51	ZA 155/800-HS; 2,5 A lub ZA 155/800-K-BSY+HS; 105 VA
2	110	100	50	1,10	0,51	0,85	0,90	53	
3	120	100	50	1,20	0,55	0,91	0,98	56	
4	130	100	50	1,30	0,59	0,98	1,07	58	
5	140	100	50	1,40	0,63	1,05	1,16	61	
6	150	100	50	1,50	0,66	1,13	1,25	63	
7	160	100	50	1,60	0,69	1,18	1,33	66	
8	170	100	50	1,70	0,73	1,26	1,41	68	
9	180	100	50	1,80	0,76	1,33	1,49	74	
10	190	100	50	1,90	0,78	1,41	1,58	73	
11	200	100	50	2,00	0,82	1,46	1,66	76	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A lub ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA
12	210	100	50	2,10	0,84	1,53	1,74	78	DXD 300/800-BSY+HS; 5A lub DXD 300/800-K-BSY+HS; 175 VA
13	220	100	50	2,20	0,88	1,61	1,83	81	
14	110	110	50	1,21	0,58	0,92	0,99	55	ZA 155/800-HS; 2,5 A lub ZA 155/800-K-BSY+HS; 105 VA
15	120	110	50	1,32	0,62	0,99	1,08	58	
16	130	110	50	1,43	0,67	1,07	1,19	60	
17	140	110	50	1,54	0,71	1,14	1,28	63	
18	150	110	50	1,65	0,76	1,22	1,37	65	
19	160	110	50	1,76	0,79	1,30	1,46	68	
20	170	110	50	1,87	0,84	1,37	1,55	70	
21	180	110	50	1,98	0,87	1,45	1,64	73	
22	190	110	50	2,09	0,92	1,53	1,73	75	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A lub ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA
23	200	110	50	2,20	0,95	1,61	1,83	77	DXD 300/800-BSY+HS; 5 A lub DXD 300/800-K-BSY+HS; 175 VA
24	210	110	50	2,31	0,97	1,66	1,92	80	
25	220	110	50	2,42	1,02	1,74	2,01	83	
26	115	115	50	1,32	0,65	0,99	1,08	58	ZA 155/800-HS; 2,5 A lub ZA 155/800-K-BSY+HS; 105 VA
27	120	120	50	1,44	0,71	1,08	1,20	61	ZA 155/1000-HS; 2,5 A lub ZA 155/1000-K-BSY+HS; 105 VA
28	130	120	50	1,56	0,75	1,15	1,29	63	
29	140	120	50	1,68	0,81	1,24	1,39	66	
30	150	120	50	1,80	0,85	1,31	1,49	68	
31	160	120	50	1,92	0,90	1,40	1,59	71	
32	170	120	50	2,04	0,94	1,49	1,69	73	
33	180	120	50	2,16	0,99	1,56	1,79	76	DXD 300/1000-BSY+HS; 5 A ZA 155/1000-HS; 2,5 A lub ZA 155/1000-K-BSY+HS; 105 VA DXD 300/1000-K-BSY+HS; 175 VA
34	190	120	50	2,28	1,03	1,64	1,89	78	DXD 300/1000-BSY+HS; 5 A lub DXD 300/1000-K-BSY+HS; 175 VA
35	200	120	50	2,40	1,08	1,73	1,99	81	
36	210	120	50	2,52	1,11	1,81	2,09	83	
37	220	120	50	2,64	1,16	1,90	2,19	86	
38	125	125	50	1,56	0,77	1,16	1,30	63	
39	130	130	50	1,69	0,85	1,25	1,40	65	ZA 155/1000-HS; 2,5 A lub ZA 155/1000-K-BSY+HS; 105 VA
40	140	130	50	1,82	0,89	1,33	1,51	68	
41	150	130	50	1,95	0,96	1,42	1,62	70	
42	160	130	50	2,08	1,00	1,52	1,73	73	
43	170	130	50	2,21	1,06	1,59	1,83	75	DXD 300/1000-BSY+HS; 5 A ZA 155/1000-HS; 2,5 A lub ZA 155/1000-K-BSY+HS; 105 VA DXD 300/1000-K-BSY+HS; 175 VA
44	180	130	50	2,34	1,10	1,68	1,94	78	DXD 300/1000-BSY+HS; 5 A lub DXD 300/1000-K-BSY+HS; 175 VA
45	190	130	50	2,47	1,16	1,78	2,05	80	
46	200	130	50	2,60	1,20	1,87	2,16	83	
47	210	130	50	2,73	1,26	1,94	2,27	85	
48	220	130	50	2,86	1,29	2,03	2,37	88	
49	140	140	50	1,96	1,00	1,43	1,63	71	ZA 155/1000-HS; 2,5 A lub ZA 155/1000-K-BSY+HS; 105 VA
50	150	140	50	2,10	1,05	1,51	1,74	73	
51	160	140	50	2,24	1,12	1,61	1,86	76	DXD 300/1000-BSY+HS; 5 A ZA 155/1000-HS; 2,5 A lub ZA 155/1000-K-BSY+HS; 105 VA DXD 300/1000-K-BSY+HS; 175 VA
52	170	140	50	2,38	1,17	1,71	1,98	78	DXD 300/1000-BSY+HS; 5 A lub DXD 300/1000-K-BSY+HS; 175 VA
53	180	140	50	2,52	1,23	1,81	2,09	81	
54	190	140	50	2,66	1,28	1,89	2,21	83	
55	200	140	50	2,80	1,34	1,99	2,32	85	DXD 300/1000-BSY+HS; 5 A lub DXD 300/1000-K-BSY+HS; 175 VA
56	150	150	50	2,25	1,15	1,62	1,87	76	
57	160	150	50	2,40	1,22	1,73	1,99	79	
58	170	150	50	2,55	1,28	1,81	2,12	81	
59	180	150	50	2,70	1,35	1,92	2,24	84	
60	190	150	50	2,85	1,43	2,02	2,37	86	
61	160	160	50	2,56	1,33	1,82	2,12	81	
62	170	160	50	2,72	1,39	1,93	2,26	83	
63	180	160	50	2,88	1,47	2,04	2,39	89	

* ciężar klapy netto = ciężar klapy brutto (klapy pakowane są w folię bąbelkową); w przypadku klap z owiewkami należy dodać 4 kg.